

TTS27NS / VS Series => XNCHH; XTCHH

High precision Temperature Compensated Crystal Oscillator

Features

Ultra-compact (2.5 x 2.0), lowest height, light weight and low current consumption.
 Low frequency is available. Using built in 1/2 frequency divide down function.
 Reflow solderable, ceramic SMD package base offers superior flatness.

Applications

Suitable for cell phone, base station, GPS and mobile radio application. RoHS compliant

Specifications

Item	Symbol	Specifications		Conditions
		TTS27NSH (TCXO)	TTS27VSH (VC-TCXO)	
Output frequency	f_0	10.0 MHz to 52.0 MHz		
Supply voltage	Vcc	+1,8V to 3.7V		
Current consumption	Icc	2.0 mA max.		Vcc=3.0V , 10 kOhm//10 pF
Output voltage	Vpp	0.8V min.		NOTE1)DC coupling
Load	Load_R,C	10kOhm // 10 pF		
Frequency stability				
/ Frequency tolerance	f_{tol}	$\pm 2.0 \times 10^{-6}$ max.		after reflow, @ 25 °C
/ Temperature	f_{0_Tc}	$\pm 0.5 \times 10^{-6}$ max.		-30 °C to +85 °C
/ Voltage coefficient	f_{0_Vcc}	$\pm 0.2 \times 10^{-6}$ max.		@3.0V \pm 5%
/ Load coefficient	f_{0_Load}	$\pm 0.2 \times 10^{-6}$ max.		@(10kOhm // 10pF) \pm 5%
/ Frequency aging	f_{age}	$\pm 1.0 \times 10^{-6}$ max.		1 year, @ 25 °C
Frequency control range	f_{cont}	---	± 3 to $\pm 15 \times 10^{-6}$	Vc=1.5V \pm 1.0V, positive polarity

NOTE 1) DC-cut capacitor of output is not put in TCXO. Please add DC-cut capacitor (1,000pF) in oscillator output line.


Phase Noise

Frequency Offset (Hz)	Phase Noise (dBc/Hz)
100	-110 typ.
1k	-130 typ.
10k	-145 typ.
100k	-145 typ.

at $f_0=24.5535\text{MHz}$ (25 \pm 2°C)



*Please consult us for customized specifications.

Outline




Pin Connections

- ① : Vc (VSB)
NC or GND (NSB)
- ② : NC or GND
- ③ : GND
- ④ : OUT
- ⑤ : NC or GND
- ⑥ : Vcc



Recommended land pattern (Top View)



unit (mm)